

# MICRO PACKAGE.

When size and length matters, the Micro30™ in the short configuration adds less than a mere 3.5" to the end of the muzzle device. Need to go quieter? Add the ADAPT™ module to the Micro30 for additional suppression in seconds compared to waiting months for another can. Bring the Micro30 along for your hunting, competition and tactical exploit.



### **TOP FEATURES**



### Strategically Placed Engraving

We strategically place the serialized engraving over the thickest Stainless Steel cross section of the suppressor. This allows fast and easy repairs should the suppressor become damaged beyond repair.



## **ADAPT™ Modular Technology**

Now you don't have to choose between a short rifle suppressor and a long one. With ADAPT™ Modules you get two lengths with one tax stamp. So you can have a shorter and lighter suppressor in seconds compared to months.



### Dual Taper Locking System™

Our quick detach mounts feature 2 tapers. The front taper provides a concentric lock up and protects the threads from carbon build up. The rear taper prevents the suppressor from loosening during firing.



### **Belt Fed Rated®**

The Surge762 is machined from top of the line materials to not only last a lifetime, but withstand any rate of fire. The Surge762 is Belt Fed Rated® and rated for calibers up to 300RUM; with no barrel length restrictions. Because we believe your gear shouldn't be what's holding you back.







# 5"

### **SPECIFICATIONS**

CALIBER: 7.62mm rated to .300 RUM; Belt Fed Rated®

DIAMETER: 1.5"

LENGTH:

Standard Configuration: 6.5" Short Configuration: 5"

WEIGHT:

Standard Configuration: 15.1oz Short Configuration: 11.8 oz

AT EAR dB: 135dB

### **MATERIALS**

Baffles: Cobalt 6

Tube: 17-4 Stainless Steel

Mount: 17-4 Stainless Steel

Finish: High Temp Cerakote®

### **FEATURES**

Reduced Gas Blowback

ADAPT™ Modular Technology

**Accuracy Comes Standard** 

**Dual Taper Locking System** 

Strategically Placed Engraving

Interchangeable End Caps

Belt Fed Rated®

### INCLUDES

7.62 R3 Flash Hider (5/8×24 Thread Pitch)

7.62 Front Cap

Micro30 Suppressor

**ADAPT Module** 

Operator's Manual

Dual Taper Lock™ Mounting Instructions

Rugged Suppressors Sticker

Micro30 Sticker

### ACCESSORIES

### **MUZZLE DEVICES:**

M2 Brake - 5/8×24

R3 Flash Mitigation System - 7.62

R3L Flash Mitigation System - 5/8×24

R3 Flash Mitigation System – 1/2×28 (5.56)

3 Port Brake

2 Port Brake - 1/2×28 (5.56)

### **END CAPS:**

5.56 Front Cap

Flash Hider Front Cap

Ti Front Cap – 7.62mm







